

Araldite®



Strength in bonding **2000+**

Expanded capabilities for composites, plastics and metals bonding

Multi purpose adhesives

Araldite® 2011

Two component epoxy adhesive

- Multi purpose
- Long working life
- Good resistance to dynamic loading

Araldite® 2029

Two component gap filling polyurethane adhesive

- Medium open time
- Designed to bond composites and metals
- Adhesion to copper and brass

NEW

Araldite® 2047

Methacrylate adhesive requiring minimal surface pretreatment

- Requires minimal surface treatment
- Good properties on otherwise difficult to bond substrates
- Good performance particularly at low temperatures

Flexible adhesives

Araldite® 2018

Two component PU adhesive system

- Good UV stability
- Ideal for bonding thermoplastics
- Flexible

Araldite® 2045

Two component flexible polyurethane adhesive

- Ideal for bonding thermoplastics and thermosets
- Fast setting
- Gap filling properties

NEW

Chemical/temperature resistant adhesives

Araldite® 2013

Two component epoxy paste adhesive

- Metal coloured paste
- Suitable for vertical applications
- Good environmental and chemical resistance

Araldite® 2014-1*

Two component epoxy paste adhesive

- Grey paste
- High temperature and chemical resistance
- Very resistant to water and a variety of chemicals

Araldite® 2052

Methacrylate adhesive with good thermal stability

- Fast curing
- Very high temperature resistance
- Excellent chemical resistance



Toughened adhesives

Araldite® 2015

Two component epoxy paste adhesive

- Toughened paste
- Ideal for bonding GRP, SMC and dissimilar substrates
- Gap filling, non sagging up to 10 mm thickness

Araldite® 2021

Two component toughened methacrylate adhesive system

- Rapid curing
- High peel strength
- Excellent bond to a wide range of plastics, composites and metals

Araldite® 2022

Two component toughened methacrylate adhesive system

- Good sanding properties
- Ideal for bonding thermoplastics
- Excellent resistance to petrol and oils

Araldite® 2031

Black epoxy paste adhesive system

- Thixotropic – non slumping
- Toughened adhesive, resilient bond
- Suitable for metal and composite bonding, good adhesion onto polyamides

NEW

Araldite® 2048

Two component toughened methacrylate adhesive system

- Tolerant to “less than ideal” pretreatment
- Gap filling up to 8 mm
- Tough flexible bonds for use in dynamic environment

NEW

Rapid cure adhesives

Araldite® 2010-1

Two component fast toughened epoxy paste adhesive

- Fast curing
- Toughened
- High shear and peel strength

Araldite® 2012

Two component epoxy paste adhesive

- Fast curing
- General purpose
- Bonds a wide variety of materials

Araldite® 2028

Two component transparent polyurethane adhesive

- Flexible
- Fast curing
- UV stable

NEW

Distributed by

EUROPE / AFRICA

Huntsman Advanced Materials (Switzerland) GmbH
Klybeckstrasse 200, P.O. Box, 4002 Basel, Switzerland
Tel +41 61 299 11 11, Fax +41 61 299 11 12

INDIA / MIDDLE EAST

Huntsman Advanced Materials (India) Pvt. Ltd
5th Floor, Bldg. No. 10, Solitaire Corporate Park,
167, Guru Hargovindji Marg, Chakal Andheri (East), Mumbai - 400 093, India
Tel +91 22 4095 1556 - 60, Fax +91 22 4095 1300/1400/1500

ASIA / PACIFIC

Huntsman Advanced Materials (Hong Kong) Ltd
Suites 3 - 12, Level 41, Langham Place, 8 Argyle Street, Kowloon, Hong Kong
Tel +852 2148 8800, Fax +852 2424 1741

AMERICAS

Huntsman Advanced Materials Americas Inc.
10003 Woodloch Forest Drive, The Woodlands, Texas 77380, USA
Tel +1 888 564 9318, Fax +1 281 719 4047

More detailed information about these products can be found on our website:
www.araldite2000plus.com

For any other information, please send an e-mail to:
araldite2000plus@huntsman.com

Ref.Nr. AdMat Araldite2000plus Range 03.09_EN

All trademarks mentioned are either property of or licensed to Huntsman Corporation or an affiliate thereof.

Sales of the product described herein (“Product”) are subject to the general terms and conditions of sale of either Huntsman Advanced Materials LLC, or its appropriate affiliate including without limitation Huntsman Advanced Materials (Europe) BVBA, Huntsman Advanced Materials Americas Inc., or Huntsman Advanced Materials (Hong Kong) Ltd. (“Huntsman”). The following supercedes Buyer’s documents.

While the information and recommendations included in this publication are, to the best of Huntsman’s knowledge, accurate as of the date of publication, NOTHING CONTAINED HEREIN IS TO BE CONSTRUED AS A REPRESENTATION OR WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, NONINFRINGEMENT OF ANY INTELLECTUAL PROPERTY RIGHTS, OR WARRANTIES AS TO QUALITY OR CORRESPONDENCE WITH PRIOR DESCRIPTION OR SAMPLE, AND THE BUYER ASSUMES ALL RISK AND LIABILITY WHATSOEVER RESULTING FROM THE USE OF SUCH PRODUCT, WHETHER USED SINGLY OR IN COMBINATION WITH OTHER SUBSTANCES. No statements or recommendations made herein are to be construed as a representation about the suitability of any Product for the particular application of Buyer or user or as an inducement to infringe any patent or other intellectual property right. Data and results are based on controlled conditions and/or lab work. Buyer is responsible to determine the applicability of such information and recommendations and the suitability of any Product for its own particular purpose, and to ensure that its intended use of the Product does not infringe any intellectual property rights.

The Product may be or become hazardous. Buyer should (i) obtain Material Safety Data Sheets and Technical Data Sheets from Huntsman containing detailed information on Product hazards and toxicity, together with proper shipping, handling and storage procedures for the Product, (ii) take all steps necessary to adequately inform, warn and familiarize its employees, agents, direct and indirect customers and contractors who may handle or be exposed to the Product of all hazards pertaining to and proper procedures for safe handling, use, storage, transportation and disposal of and exposure to the Product and (iii) comply with and ensure that its employees, agents, direct and indirect customers and contractors who may handle or be exposed to the Product comply with all safety information contained in the applicable Material Safety Data Sheets, Technical Data Sheets or other instructions provided by Huntsman and all applicable laws, regulations and standards relating to the handling, use, storage, distribution and disposal of and exposure to the Product.

Please note that products may differ from country to country. If you have any queries, kindly contact your local Huntsman representative.

© 2009 Huntsman Corporation. All rights reserved.