

Mobil Delvac 1 LE 5W-30 Claims Enhancement

Summary

From April 2013, the performance claims profile of Mobil Delvac1 LE 5W-30 as a SAE 5W-30 fuel economy, heavy duty diesel engine oil will be significantly improved to widen its scope of application.

Mobil Delvac 1 LE 5W-30 is a fully synthetic, heavy-duty diesel engine oil that combines advanced engine protection for modern low emissions vehicles with enhanced fuel economy potential¹ and other sustainability-related benefits such as engine durability, emissions system protection and extended drain capability. It uses state-of-the-art technology to deliver exceptional performance and is well suited for an extensive array of diesel-powered commercial vehicles for both on- and off-highway use.

Please view the on-line ExxonMobil Product Data Sheet.

¹Relative to a conventional 15W-40 engine oil – Actual fuel economy improvement is dependent on vehicle/equipment type, outside temperature, driving conditions and your current fluid viscosity.

Introduction Timing of New Claims Profile

The current claims profile of Mobil Delvac 1 LE 5W-30 will be formally canceled on 1st April 2013, but will continue to be available from ExxonMobil in order to deplete inventory.

Quality and Performance Claims

Mobil Delvac 1 LE 5W-30 will have the following performance profile that is required for a vast majority of Euro V & VI engines. (In red are claims added to current existing claims profile.)

Meets or exceeds the requirements of:
ACEA E9/ E7/E6
API CJ-4 ; API SN
JASO DH-2
Caterpillar ECF-3
Cummins CES 20081
DAF Extended Drain
Ford WSS-M2C171-E
has the following builder approvals:
MB-Approval 228.51/ 228.31
MAN M 3477
Volvo VDS-4 / VDS-3
Deutz DQC IV-10 LA
Detroit Diesel DDC Power Guard Oil Specification 93K218
Mack EO-O Premium Plus
MTU Oil Category 3.1
Renault Truck RLD-3/ RLD-2
is recommended by ExxonMobil for use in applications requiring:
Renault Trucks RXD/RGD

Product Data Sheet (PDS)

The revised ExxonMobil PDS of Mobil Delvac 1 LE 5W-30 will be available online in the next few months.

Material Safety Data Sheet (MSDS)

The revised [MSDS](#) of Mobil Delvac 1 LE 5W-30 will be available online at the same time as the product becomes available for ordering.

Pack Labels

Furthermore, you will be pleased to note that new labels for 20L pails and 4L bottles for the new Mobil Delvac 1 LE 5W-30 have been designed alongside the revised claims performance profile enhancement.

Material Codes

The new article list is as follows and also the mapping table. Please note that * will be removed in the article descriptor once old article stocks are depleted.

152254 M-DELVAC 1 LE 5W30* IBC-PL 1000L
 152249 M-DELVAC 1 LE 5W30* PAIL 20L
 152250 M-DELVAC 1 LE 5W30* DRUM-M 208L
 152251 M-DELVAC 1 LE 5W30*
 152252 M-DELVAC 1 LE 5W30 4X4L EU-ML
 152253 M-DELVAC 1 LE 5W30 PAIL 20L D/AT

New Material	New Description	Replacing Material	Current Replacement Description
151280	M-DELVAC 1 LE 5W30 IBC-PL 1000L	152254	M-DELVAC 1 LE 5W30*IBC-PL 1000L
150685	M-DELVAC 1 LE 5W30 PAIL 20L	152249	M-DELVAC 1 LE 5W30* PAIL 20L
150684	M-DELVAC 1 LE 5W30 DRUM-M 208L	152250	M-DELVAC 1 LE 5W30* DRUM-M 208L
150683	M-DELVAC 1 LE 5W30	152251	M-DELVAC 1 LE 5W30*

Please note that orders for the new article codes will only be accepted from distributors when the current stocks are fully depleted in the ExxonMobil warehouses. The new codes will be opened once depletion is completed.

Further Information

For further information on this exciting new development for Mobil Delvac 1 LE 5W-30 and for Mobil branded Commercial Vehicle Lubricants in general in EAME, please contact your local Distributor Business Consultant or Dedicated Customer Professional.

**These front labels refer to all countries except Central Europe.*

Information

Download and share this article
 DE | [EN](#) | FR | IT | PL | TR

