

Product information

No. 67134000

KAJO-Chisel Paste

KAJO-Chisel Paste is made of a lithium complex soap grease based on mineral oil. It contains a solid lubricant combination of copper/graphite and molybdenum disulfide. This guarantees a safe parting efficiency and wear reduction at large contact pressures and temperatures up to 1100° C.

Practical advantages:

KAJO-Chisel Paste is used in socket tools and wearing bushings of hydraulic and compressed air hammers.

The critical wear point is between the socket end of the chisel and the guiding sleeve. The extreme contact pressures and temperatures occurring in this area make high demands on **KAJO-Chisel**

Paste. **KAJO-Chisel Paste** proved to be very efficient for these applications.

Properties:

- high load-carrying capacity
- good corrosion protection
- good water resistance
- good parting efficiency
- wear reduction
- oxidation resistance

Ratings:

Properties	Value	Unit	Standard
Colour	coppery/grey		
NLGI-class	2		DIN 51 804
Worked penetration	265 - 295	0,1 mm	ASTM D 217
Dropping point	>180	°C	ASTM D 556
VKA OK-load Welding load	4600 4800	N	DIN 51 350 T4
Base oil viscosity at 40 °C	120	cSt	DIN 51 562
Load capacity acc. to Brugger	45	N/mm ²	DIN 51 347
Operating temperature range	-20 up to +1100	°C	

Version 2

revised: 19.06.2015 DR/MJ/Pos/AO

- All ratings are average values and are subject to production-related variations –