

# TECHNICAL DATA SHEET

## TB-338 Tryk-Booster

### Description

TB-338 removes dust and other dry foreign matters from electronics, photographic equipment, optics, clockworks, modules, instruments, glass, sewing machines, copiers, printers, radio- and TV-sets, VCRs and similar sensitive equipment.

Can be mounted with extension tube for use in hard-to-reach areas and for applications which require precision. TB-338 is not harmless to plastics and metal etc.

### Properties

- for hardware and other electronic components
- removes dust and dirt
- for gentle cleaning
- pressure 5 bar
- extension tube enclosed

### Application

Hold the can vertical and spray from side to side or up and down.  
Do not hold the can horizontal or turn it upside down.

In areas with the risk of ignition use TL-676.

**Note:** Be sure that the treated area is well ventilated before switching on power.





# TECHNICAL DATA SHEET

## TB-338 Tryk-booster

### Technical and physical data

Partnumber	19835
Packing	spray
Contents	500 ml
Weight	307 g
Colour	clear/transparent
Propellant	propane/butane
Base (konc)	wax
Density at 15°C	0,615 g/ml
Heatresistance	60 °C
Soluble in	petrol
Consistency	dry and wax-like
Dust dry	about 5 minutes
Full strength/ full hardened	5-10 minutes
Coverage	4-5m <sup>2</sup>
Emptying rate	1,02 g/sec
FDA-CFR	172886 and 1783710