

# An excellent choice for lubricating food & beverage processing equipment

Food and beverage processing facilities face unique challenges, including the need for lubricants that fight corrosion, resist water washout and thrive under wide temperature ranges – all while also meeting stringent certification standards and regulations. Many MOLYKOTE® Lubricants conform to requirements under U.S. FDA 21 CFR 178.3570 and are NSF H1 or H2 certified or meet NSF/ANSI Standard 51 or NSF/ANSI CAN Standard 61; many also are Kosher, Pareve and Halal certified.

In this document, you will learn more about our solutions for the food and beverage industry, including greases, pastes, oils, compounds and dispersions for a variety of equipment and components. Pages 2 and 3 offer you a variety of MOLYKOTE® products to meet the demands of your mills, pumps, compressors, flanges, mixers, cooking kettles, conveyor systems, molds, ovens, packaging lines and electrical substations.



# MOLYKOTE® solutions for food & beverage processing facilities

## Mill

- Bearings<sup>(A)</sup>
- Gears & gearbox(C)
- Chains(B)
- Seals & gaskets<sup>(D)</sup>
- Threaded connections(E)
- Blowers

MOLYKOTE® L-1115 FM Synthetic Gear Oil

- Blower bearings<sup>(A)</sup>
- Compressor

MOLYKOTE® L-1232FM Synthetic Compressor Oil or MOLYKOTE® L-1246FM Synthetic Compressor Oil

- Compressor bearings(A)
- Compressor seals(D)

## 2 Pump, compressor & flanges

Pump

MOLYKOTE® L-1668FM Synthetic Blend Vacuum Pump Oil

- Pump bearings<sup>(A)</sup>
- Pump seals<sup>(D)</sup>
- Compressor

MOLYKOTE® L-1232FM Synthetic Compressor Oil or MOLYKOTE® L-1246FM Synthetic Compressor Oil

- Compressor bearings<sup>(A)</sup>
- Compressor seals<sup>(D)</sup>
- Flange threaded connections(E)
- Flange seals(D)

## 3 Mixer & cooking kettles

- Bearings<sup>(A)</sup>
- Seals(D)
- Chain drives<sup>(B)</sup>
- Threaded connections<sup>(E)</sup>
- Gears & gearbox<sup>(C)</sup>
- Inner wall & mixing tool MOLYKOTE® Separator Silicone Spray or MOLYKOTE® 316 Silicone Release Fluid
- 4 Conveyor system, including molds
  - Bearings, rollers & pulleys(A)
  - Chains & sprockets(B)
  - Gearboxes<sup>(C)</sup>
  - Belt tensioner(B)(C)(E)
  - Fasteners(E)
  - Molds & filling spouts MOLYKOTE® Separator Silicone Spray or
  - MOLYKOTE® 316 Silicone Release Fluid • Slide rails, plates & tracks

Liquids: MOLYKOTE® 557 Silicone Dry Film Lubricant or MOLYKOTE® 316 Silicone Release Fluid

Sprays: MOLYKOTE® 557 Silicone Dry Film Lubricant (Aerosol), MOLYKOTE® Separator Silicone Spray or MOLYKOTE® 316 Silicone Release Fluid Spray

• Spiral freezer(A)(B)(C)

## **5** Oven


- Bearings (conveyor roller, trolley, fan blower)(A)
- Slide rails & tracks

See "Slide rails, plates & tracks" under "Conveyor system, including molds" at lower left

· Door hinges & latches

MOLYKOTE® Food Machinery Oil Spray

- Chains(B)
- Seals(D)



6 Packaging

 Heat seal equipment (bars) MOLYKOTE® 316 Silicone Release Fluid Spray,

MOLYKOTE® Separator Silicone Spray, MOLYKOTE® 7 Release Compound or MOLYKOTE® 316 Silicone Release Fluid

Conveyors

See "Conveyor system, including molds" at left

Gearboxes<sup>(C)</sup>

## **Electrical substation**

• Gaskets & seals

MOLYKOTE® 3099 HVIC Compound\* or MOLYKOTE® 111 Compound

Switches

MOLYKOTE® Cu-7439 Plus Paste V1\*, MOLYKOTE® 41 Extreme High Temperature Grease\*, MOLYKOTE® 44 Medium High Temperature Grease\*, MOLYKOTE® 33 Medium Extreme Low Temperature Grease\* or MOLYKOTE® 3451 Chemical Resistant Bearing Grease\*

Switch gears

MOLYKOTE® 111 Compound

· High-voltage electrical contacts

MOLYKOTE® HP-300 Grease or MOLYKOTE® G-5008 Dielectric Grease\*

\*This lubricant does not possess food industry certification. It should only be used in applications in which it will not have any contact with food.

## General components


# (A)Bearings

#### Standard

MOLYKOTE® G-0050 FM White EP Bearing Grease, MOLYKOTE® G-0051 FM White EP Bearing Grease, MOLYKOTE® G-0052 FM White EP Bearing Grease, MOLYKOTE® G-1502 FM Synthetic Bearing & Gear Grease, MOLYKOTE® G-4500 FMS Multi-Purpose Synthetic Grease or MOLYKOTE® G-4501 FMS Multi-Purpose Synthetic Grease

Extreme temperatures

MOLYKOTE® HP-300 Grease or MOLYKOTE® HP-500 Grease



## (E)Threaded connections

• MOLYKOTE® P-1900 FM Anti-Seize Paste or MOLYKOTE® P-1900 FM Paste Spray



#### Cleaner

MOLYKOTE® Foam Cleaner Spray



### (B)Chains

- Non-dripping & extremely tacky MOLYKOTE® G-1502 FM Synthetic Bearing & Gear Grease
- Extreme temperatures MOLYKOTE® L-1468 FM Synthetic Freezer Chain Oil
- Spray

MOLYKOTE® Food Machinery Oil Spray



- Helical, helical bevel, planetary & cycloidal gear reducers
- MOLYKOTE® L-1115 FM Synthetic Gear Oil or MOLYKOTE® L-1122 FM Synthetic Gear Oil Worm gears
- MOLYKOTE® L-1146FM Synthetic Extreme Temp Gear Oil
- Oil lubrication standard MOLYKOTE® L-1115 FM Synthetic Gear Oil or MOLYKOTE® L-1122 FM Synthetic Gear Oil
- Oil lubrication extreme temperatures MOLYKOTE® L-1146FM Synthetic Extreme Temp Gear Oil
- Grease

MOLYKOTE® G-1502 FM Synthetic Bearing & Gear Grease, MOLYKOTE® G-4500 FMS Multi-Purpose Synthetic Grease or MOLYKOTE® G-4501 FMS Multi-Purpose Synthetic Grease

Spray

MOLYKOTE® Food Machinery Oil Spray



## Standard

MOLYKOTE® 111 Compound

• Extreme temperatures MOLYKOTE® HP-300 Grease

· Chemical resistance MOLYKOTE® HP-300 Grease


 Vacuum MOLYKOTE® High Vacuum Grease

Anti-stick

MOLYKOTE® Separator Silicone Spray or MOLYKOTE® 316 Silicone Release Fluid

· Mechanical seal

MOLYKOTE® L-1605 FM Synthetic Barrier Fluid



# For more information

View food & beverage certifications for our lubricants:



Explore our food & beverage lubricants web page:



View MOLYKOTE® products' technical data sheets (TDS):



Featured MOLYKOTE® products for food & beverage processing  GREASES  OILS			
G-0050 FM White EP Bearing Grease G-0051 FM White EP Bearing Grease G-0052 FM White EP Bearing Grease G-1502 FM Synthetic Bearing & Gear Grease G-4500 FMS Multi-Purpose Synthetic Grease G-4501 FMS Multi-Purpose Synthetic Grease G-5008 Dielectric Grease*	HP-300 Grease HP-500 Grease 33 Medium Extreme Low Temperature Grease* 41 Extreme High Temperature Grease* 44 Medium High Temperature Grease* 3451 Chemical Resistant Bearing Grease*	Food Machinery Oil Spray Separator Silicone Spray L-1115 FM Synthetic Gear Oil L-1122 FM Synthetic Gear Oil L-1146FM Synthetic Extreme Temp Gear Oil	L-1232FM Synthetic Compressor Oil L-1246FM Synthetic Compressor Oil L-1468 FM Synthetic Freezer Chain Oil L-1605 FM Synthetic Barrier Fluid L-1668FM Synthetic Blend Vacuum Pump Oil
COMPOUNDS	DISPERSIONS	PASTES	ANTI-FRICTION COATINGS
High Vacuum Grease 4 Electrical Insulating Compound 7 Release Compound 111 Compound 3099 HVIC Compound*	316 Silicone Release Fluid 316 Silicone Release Fluid Spray 557 Silicone Dry Film Lubricant 557 Silicone Dry Film Lubricant (Aerosol)	Cu-7439 Plus Paste V1* P-1900 FM Anti-Seize Paste P-1900 FM Paste Spray	N/A

<sup>\*</sup>This lubricant does not possess food industry certification. It should only be used in applications in which it will not have any contact with food.

# **About MOLYKOTE® Specialty Lubricants**

Since 1948, customers around the world have trusted the MOLYKOTE® brand for performance and expertise to help solve complex, technical design and lubrication challenges. To learn more about our extensive product and service offering, to utilize our interactive product selection tool, or to locate a distributor, visit **molykote.com**.





We have Contact Centers around the globe. Find the phone number for the center nearest you at **www.dupont.com/molykotecontact**.



Phone: 0046 8 - 703 02 00 info@galindberg.se



## **MOLYKOTE**

DuPont", the DuPont Oval Logo, and all trademarks and service marks denoted with  $^{m}$ ,  $^{so}$  or  $^{\circ}$  are owned by affiliates of DuPont de Nemours, Inc. unless otherwise noted.  $^{\circ}$  2025 DuPont.

The information set forth herein is furnished free of charge and is based on technical data that DuPont believes to be reliable and falls within the normal range of properties. It is intended for use by persons having technical skill, at their own discretion and risk. This data should not be used to establish specification limits nor used alone as the basis of design. Handling precaution information is given with the understanding that those using it will satisfy themselves that their particular conditions of use present no health or safety hazards. Since conditions of product use and disposal are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information. As with any product, evaluation under end use conditions prior to specification is essential. Nothing herein is to be taken as a license to operate or a recommendation to infringe on patents.

Form No. 01-2042-01-AGP0725 #17601M-68