

MOLYKOTE[®] 7508 Valve Grease

Silicone-based semi-fluid lubricating grease, designed for ceramic discs in water taps, faucets and valves

Features

- Wide service-temperature range: -40°C to 200°C (-40°F to 392°F)
- Helps prevent hard water residues on ceramic valve components
- Resists water washout
- Helps extend the service life of ceramic discs
- Meets NSF/ANSI 61 standard

Composition

- Silicone oil
- White solid lubricant
- Sedimentation inhibitor

Applications

Lubrication for ceramic discs of water taps and faucets, especially for single-lever mixers. Can be applied to rubber gaskets and plastic components.

Description

MOLYKOTE[®] 7508 Valve Grease is tacky, nonmelting silicone grease. It has been designed to lubricate ceramic discs of water faucets, particularly single-lever mixer taps.

How to use

Prior to use, mix any visible base oil back into the grease and clean application area thoroughly. Apply product with brush, spatula, or dispensing equipment.

Handling precautions

MOLYKOTE[®] 7508 Valve Grease may cause temporary discomfort when in direct contact with skin or eyes. In case of skin or eye contact, immediately rinse thoroughly after handling.

PRODUCT SAFETY INFORMATION REQUIRED FOR SAFE USE IS NOT INCLUDED IN THIS DOCUMENT. BEFORE HANDLING, READ SAFETY DATA SHEETS AND CONTAINER LABELS FOR SAFE USE, PHYSICAL AND HEALTH HAZARD INFORMATION.

Typical properties

Specification writers: These values are not intended for use in preparing specifications. Please contact your local MOLYKOTE[®] sales representative prior to writing specifications on this product.

Standard ⁽¹⁾	Test	Unit	Result
	Color		White
	Viscosity at 25°C	mPas	30,000-85,000
	Density	g/cm ³	1.1
	Service temperature	°C	-40 to 200
DIN 51807 pt. 1	Water resistance, static, 90°C		0

⁽¹⁾DIN: Deutsche Industrie Norm.

Usable life and storage

When stored in the original unopened containers in a cool and dark place, this product has a usable life of 36 months from the date of production.

Packaging

This product is available in different standard container sizes. Detailed container size information should be obtained from your nearest MOLYKOTE[®] sales office or MOLYKOTE[®] distributor.

DuPont™, the DuPont Oval Logo, and all trademarks and service marks denoted with ™, SM or ® are owned by affiliates of DuPont de Nemours, Inc. unless otherwise noted.
© 2012-2019 DuPont.

The information set forth herein is furnished free of charge and is based on technical data that DuPont believes to be reliable and falls within the normal range of properties. It is intended for use by persons having technical skill, at their own discretion and risk. This data should not be used to establish specification limits nor used alone as the basis of design. Handling precaution information is given with the understanding that those using it will satisfy themselves that their particular conditions of use present no health or safety hazards. Since conditions of product use and disposal are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information. As with any product, evaluation under end use conditions prior to specification is essential. Nothing herein is to be taken as a license to operate or a recommendation to infringe on patents.