PRODUCT INFORMATION

ISOCUT A 15

UNIVERSAL CUTTING OIL

DESCRIPTION

ISOCUT A 15 is a universal cutting oil suitable for a wide range of processes.

The product is suitable for machining non-ferrous metals.

It contains special additives to increase the tool life. Furthermore, ISOCUT A 15 can be used for the following processes: Turning, drilling, milling, reaming, thread forming, thread cutting, sawing, grinding and tooth flank grinding.

Very good results are achieved in critical machining operations due to the modern additives. ISOCUT A 15 can be used for a long time due to high-quality base oils.

BENEFITS

- outstanding pressure absorption capacity
- increased tool life
- low oil mist formation
- resistant to ageing

TECHNICAL DATA

Storage temperature	5 - 35 °C
Shelf life	observe the use by date on the container
Perchloroethylene compatibility for cleaning applications	✓

PHYSICAL DATA

Appearance	yellowish
Density/20 °C (ASTM D 7042)	approx. 0.850 g/cm³
Viscosity/40 °C (ASTM D 7042)	approx. 15 mm²/s
Flash point COC (ISO 2592)	> 180°C

Only valid in combination with EC Safety Data Sheet
The information given here is considered to be correct and is offered for your consideration, investigation and verification. No warranties are expressed or implied since the use of our products is beyond our control. Statements concerning the use of PETROFER products are not to be construed as recommending the infringement of any patent.
www.petrofer.com