



BETAMATE™ 2700 (A+B)

Short Description

2-component polyurethane based adhesive and sealing system. BETAMATE 2700 (A+B) is high viscous and cures independent from humidity.

Properties

- Designed for glass and structural bonding
- Long open time
- Good sagging properties
- Very good elongation properties
- Excellent long term durability under dynamic stress

Application

All Dow Automotive products are primarily developed in co-operation with the automobile manufacturers, according to their needs and their specifications, they are approved for the specific applications as defined by the customer. The use of the product other than approved application have to be released in written form by the Technical Service of Dow Automotive Systems.

Technical Data

The following technical data and information should be considered as typical only and should not be used for specification purposes. Unless specified otherwise test are conducted at 23 °C/50% relative humidity.

Basis	A: Polyurethane prepolymers	B: Polyurethane prepolymers (Accelerator)
Colour	A: black	B: black
Density	A: 1.25 g/cm ³	B: 1.28 g/cm ³
Solid contents	min 98%	
Viscosity Extrusion, Ballan at 23°C, 4mm nozzle / 4bar	A: 15 - 22 g/min	B: 9 - 17 g/min
Processing temperature	10 - 40°C	
Working time	18 -25 min	
Sagging, on vertical wall tilting	very good, non-sagging, max. 30°	
Tensile strength (DIN EN ISO 527-2)	> 5.5 MPa	
Lap shear strength (DIN EN 1465) after 24h	min 4.0 MPa	
Elongation at break (DIN EN ISO 527-2)	> 600%	
Hardness Shore A (DIN 53 505)	40 - 55	
G-Modulus (DIN EN 14869-2)	0.8 - 1.0 MPa	
Abrasion resistance	extreme high	
Temperature stability	-40 bis 100°C, short term in cured state up to 140°C	
Resistance to chemicals	Highly resistant to aqueous chemicals, petrol, alcohol and mineral oils; conditionally to esters, ketones, aromatics and chlorinated hydrocarbons. For a detailed list of tested chemicals contact our technical service.	

**Bonding surface preparation**

All bonding surfaces must be free of dirt, dust, water, oil and grease. It's recommended to use a primer or activator for the pretreatment of the bonding surfaces. Please contact our Technical Service for assistance.

Work instruction

To guarantee a homogenous mixing of the components the first 20 cm of the adhesive bead should be disposed.

Equipment to handle

BETAMATE 2700 (A+B) is mixed dynamically. A special dynamic mixing unit is part of each set.

Our electro-mechanical application device BETAGUN™ is specially designed to process the BETAMATE 2700 (A+B) sets to ensure an optimal processing and handling of the adhesive.

Cleaning

Uncured BETAMATE 2700 (A+B) can be removed with BETACLEAN 3000, 3350 or 3500. Cured BETAMATE 2700 (A+B) can only be removed mechanically. Contaminated equipment can be cleaned with BETACLEAN 3000 or 3350.

Shelf life

6 months at +5°C to +25°C in original box. Store cool and dry

Containers

2 x 290 ml cartridge set; other packings upon request

Health and Safety

The use of polyurethane adhesives is generally harmless and as long as the basic rules for safe handling of chemicals are applied. However, the direct contact of uncured adhesive with food and food containers should be avoided. It is mandatory to use protective measures in order to prevent direct skin contact. Suitable gloves and eye protection are essential. Should the skin come into contact with uncured adhesive, it must be rinsed first with warm water and then cleaned thoroughly with conventional soap. Cleaning skin with solvents must be avoided. It is essential to ensure good ventilation. For detailed protective measures refer to the Material Safety Data Sheets.

Dow Automotive Systems Quality Assurance

Quality is our utmost goal. Dow Automotive works according to a modern quality management system conforming to ISO/TS 16949:2002. All sites of Dow Automotive are conforming to ISO 14001:2004.

All statements, technical information and recommendations contained in this document are based on tests that we believe are reliable.

However, the accuracy or completeness of the statements, information and recommendations is not guaranteed, as before using, the user should determine the suitability of the product for user's intended purpose.

This document does not create any liability and all warranties, express or implied, including the implied warranties of merchantability and fitness for a particular purpose are disclaimed. Neither seller nor manufacturer shall be liable either in contract or tort for any loss or damage, direct, incidental, or consequential, arising out of the use and/or the inability to use the product. Seller's/manufacture's only obligation is the replacement of defective product.

Dow Automotive Systems Main Offices

The Dow Chemical Company Customer Information Group Europe	Dow Automotive Systems World Head Quarter	Dow Automotive Systems	Dow Automotive Systems
Phone +800 3 6946367 Phone +32 3 450 2240 Italia 800 783 825 Fax +32 3 450 2815	1250 Harmon Road Auburn Hills, MI 48326 USA Tel. +1 248 391 63 00 Fax +1 248 391 64 17	Dow Deutschland Anlagengesellschaft GmbH Am Kronberger Hang 4 65824 Schwalbach Germany Tel: +49 6196 566 0 Fax: +49 6196 566 444	Dow Europe GmbH Bachtobelstrasse 3 8810 Horgen Switzerland Tel. +41 44 728 2111 Fax: +41 44 728 2935
Dow Automotive Systems	Dow Automotive Systems	Dow Automotive Systems	Dow Automotive Systems
St. George's Way Bermuda Industrial Estate Nuneaton CV10 7QT United Kingdom Tel: + 44 24 7635 7200 Fax: + 44 24 7635 7257	Dow Chemical Ibérica, S.L. Ribera del Loira, 4-6 - Planta 4ª (Edificio IRIS) 28042 Madrid Spain Tel. + 34 91 740 7800 Fax. + 34 91 740 7785	Dow France S.A.S. 23 avenue Jules Rimet 93631 La Plaine St Denis Cedex France Tel: +33 1 49 21 78 78 Fax: +33 1 49 21 79 79	Dow Italia Divisione Commerciale s.r.l. Via F. Albani, 65 20148 Milano Italy Tel: +39 02 482 21 Fax: +39 02 482 241 08



Automotive Systems

Technical Datasheet

NOTICE: No freedom from any patent owned by Dow or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change over time, the Customer is responsible for determining whether products and the information in this document are appropriate for the Customer's use and for ensuring that the Customer's workplace and disposal practices are in compliance with the applicable laws and other governmental enactments. Dow assumes no obligations or liability for the information in this document. No warranties are given. Dow Automotive Systems is a business unit of The Dow Chemical Company.