Mobil SHC[®]

Performance by ExonMobil

Mobilith SHCTM 460 provided 88.000 \$ US /year cost savings at rolling mill bearings of an iron and steel producer*



Energy lives here"

Danieli Rolling Mill Stand Bearings | Yildiz Demir Celik | Turkey

Situation

Yildiz Demir Celik, one of the leading iron and steel producers in Turkey, uses Danieli rolling mills in production at their plant located in Kocaeli, Turkey. Another branded grease was used in the temper and skinpass bearings of the machines. The company had very frequent bearing failure due to insufficient lubrication.

Benefit

Mobilith SHC[™] 460 has helped Yildiz Demir Celik extend greasing intervals by 300%, decrease bearing failures by 94% and achieve 88.000 \$ US savings annually.

Recommendation

AD Yasar Petrol and ExxonMobil engineers recommended Mobilith SHC™ 460 synthetic grease to ensure longer lubrication intervals and to prevent production interruptions. With excellent performance even at extreme temperatures, Mobilith SHC 460 is resistant to oxidation and deterioration of structural stability, allowing extended lubrication intervals and increased equipment protection.

88.000 \$ US/year* cost savings

Industrial Lubricants

Advancing productivity

Helping you reach your Safety, Environmental Care** and Productivity goals through our innovative lubricants and services is our highest priority. That's Advancing Productivity. It's how we help you achieve your broader vision of success.

* This proof of performance is based on the experience of a single customer. Actual results can vary depending upon the type of equipment used and its maintenance, operating conditions and environment, and any prior lubricant used.

** Visit mobil.com/industrial to learn how certain Mobil-branded lubricants may provide benefits to help reduce environmental impact. Actual benefits will depend upon product selected, operating conditions and applications.

Advancing

Productivity

mobil.com/industrial

^{© 2019} Exxon Mobil Corporation. All rights reserved. All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its affiliates unless otherwise noted HIPOP 2019-603