
MOLYDUVAL
Grundo MP 68 G 1



Mineral base oil for the production of lubricants / Group 1

Paraffinic based solvent neutral oil with high viscosity index.

Characteristics

- good anticorrosive properties
- oxidation resistant
- good foam behavior
- relative low residue forming
- good oil/water separation properties, easy drainage of excess water from lubrication systems
- high flash point
- low foam forming
- high natural VI

Applications

- for manufacturing of lubricants
- for manufacturing of release agents
- for producing chemical technical products

Technical Datas

Color		transparent
Viscosity Class	ISO-VG	68
Viscosity 40°C	mm^2/s	68
Viscosity 100°C	mm^2/s	8,7
Density 40°C	kg/m^3	890
Pour point	°C	-12
Flash Point COC	°C	> 230

For further information, please see our website www.molyduval.com or consult your local representative.

The content of this manual is based on our current knowledge and experience in the development and manufacture of lubricants. Because of the complexity of tribological systems, the effect of our products depends on many parameters, which we cannot assess and which influence we cannot evaluate. For this reason general statements about the function of our products are not possible. The information in this manual, therefore, contains non-binding guidelines, which should give the technical trained reader information on possible applications. The information in this manual does not include property assurances or warranties or guarantees to the properties or suitability of this product in a specific application. Prior to its use it is absolutely necessary to test this product in the application to ensure that the product and its use is safe, economical and fully suitable. It should proceed with due diligence. We reserve the right to change the information in this manual at any time and without notice. All previous versions of this manual are no longer valid. Updating : 17.05.2024