

ULTRAFORM 8441

Synthetic high performance lubricant

Description: ROCOL ULTRAFORM 8441 is a synthetic high performance lubricant formulated from ester oil. This product can be used as cutting and spray oil. The product has been developed for sawing operations of alloyed and high alloyed carbon steels, chrome-nickel-molybdenum-steels, nickel-alloys and titanium.

ROCOL ULTRAFORM 8441 featuring high cutting performance, outstanding tool life and minimum consumption of cutting fluid. The idea to use natural raw materials has been dominating the development of this product in order to take account of environmental thinking. Therefore, this product is biodegradable.

Properties:

- Excellent lubricating properties
- Provides long service life
- Versatile lubricant
- Easily biodegradable

Application:

ROCOL ULTRAFORM 8441 is applied straight from the package. It is applied manually or with mist lubricating systems.

Technical and physical data

Appearance:	Brown fluid
Density:	ca. 0,98 gr./ml at 20° C
Viscosity:	ca. 39 mm ² /s at 40° C
Flashpoint:	ca. 200°C
Pour point:	ca. -12°C
Copper corrosion:	Grade 3
Article no/pack sizes:	67035008 5 kg 67035009 18 kg

Information: For further technical information and/or MSDS please look at www.itw-spraytec.dk or contact our sales department (+45) 86 82 64 44

Important note: All information and technical data are based on tests which to our knowledge are correct and reliable. However, there are no guarantees. It is the responsibility of the user to make sure that the information is useable and complete in connection with the purpose in question.